


LAMP PHOTOMETRIC REPORT

MODEL: 92EL051230/WHBK		
POWER: 10W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 742.49 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	1552	1580	1449	1308	1262	1261	1297	1422	0- 10	152.8	152.8	20.6
20	763.3	791.1	711.7	643.3	627.9	621.2	618.7	701.9	10- 20	280.8	433.7	58.4
30	287.1	298.2	283.0	261.5	253.1	250.4	250.6	276.1	20- 30	202.9	636.6	85.7
40	49.86	52.08	47.15	45.73	46.35	45.47	40.92	45.66	30- 40	84.23	720.8	97.1
50	10.47	9.851	8.983	9.565	10.35	9.731	8.871	9.507	40- 50	15.78	736.6	99.2
60	2.817	2.817	2.535	2.705	2.753	2.884	2.659	2.786	50- 60	5.257	741.8	99.9
70	0.0869	0.0680	0.0572	0.0614	0.0325	0.0327	0.0572	0.0327	60- 70	0.6277	742.5	100
80	0.0163	0.0041	0	0.0068	0.0081	0.0136	0.0245	0.0109	70- 80	0.0269	742.5	100
90	0	0	0	0	0.0109	0.0068	0.0109	0.0082	80- 90	0.0065	742.5	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:08 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```