


LAMP PHOTOMETRIC REPORT

MODEL: 93ZFLD3030/BL		
POWER: 30W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 2662.8 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	2552	2814	2952	2502	2299	2583	3014	2922	0- 10	267.8	267.8	10.1
20	1766	2307	2700	2038	1688	2087	2797	2415	10- 20	695.6	963.4	36.2
30	891.9	1599	1790	1565	1180	1621	1889	1703	20- 30	875.6	1839	69.1
40	104.1	555.7	615.5	629.0	134.0	688.6	674.6	655.6	30- 40	602.3	2441	91.7
50	28.03	61.68	127.4	67.07	33.98	74.01	121.6	72.11	40- 50	175.9	2617	98.3
60	9.946	13.46	27.82	13.98	11.40	14.57	25.56	13.95	50- 60	35.86	2653	99.6
70	1.573	2.780	4.187	2.707	2.412	2.786	3.925	2.729	60- 70	8.823	2662	100
80	0.1158	0.1589	0.1857	0.1503	0.1210	0.1331	0.1640	0.1408	70- 80	0.8261	2663	100
90	0.0834	0.0950	0.1311	0.1025	0.1210	0.1358	0.1612	0.1394	80- 90	0.1381	2663	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:30 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```