


LAMP PHOTOMETRIC REPORT

MODEL: 95Livial60/GR		
POWER: 10W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 850.49 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	399.5	399.1	399.1	398.8	398.0	398.2	399.9	402.1	0- 10	38.45	38.45	4.52
20	373.9	371.4	372.9	372.2	372.0	373.5	376.7	376.8	10- 20	109.6	148.1	17.4
30	328.4	326.3	325.5	326.1	326.1	330.9	333.4	333.2	20- 30	162.6	310.7	36.5
40	262.2	259.1	257.5	260.3	263.2	268.0	270.8	269.4	30- 40	186.4	497.2	58.5
50	177.3	174.1	172.1	171.1	171.8	179.6	187.5	185.3	40- 50	171.3	668.4	78.6
60	83.29	82.37	81.13	79.26	82.91	88.35	91.45	90.04	50- 60	115.7	784.1	92.2
70	25.86	24.65	24.84	24.45	24.96	27.40	29.12	28.27	60- 70	51.58	835.7	98.3
80	3.786	3.527	3.324	3.345	3.380	3.700	4.033	4.124	70- 80	12.81	848.5	99.8
90	0.2055	0.2218	0.2212	0.2256	0.1701	0.1920	0.1884	0.1995	80- 90	1.979	850.5	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:23 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```