


LAMP PHOTOMETRIC REPORT

MODEL: 95Livia90/BL		
POWER: 6W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 441.83 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	389.8	389.5	378.9	367.8	366.5	370.8	376.8	383.3	0- 10	38.15	38.15	8.64
20	293.4	295.9	281.3	266.4	264.4	270.2	279.9	289.4	10- 20	92.28	130.4	29.5
30	196.1	198.7	188.9	173.9	171.8	176.4	185.1	194.8	20- 30	105.9	236.3	53.5
40	122.3	124.2	116.9	104.3	105.0	107.6	111.8	119.2	30- 40	92.09	328.4	74.3
50	71.49	72.24	65.67	58.20	59.91	60.94	61.67	66.31	40- 50	67.33	395.7	89.6
60	36.55	36.77	32.54	29.03	30.14	30.56	30.14	32.58	50- 60	42.24	438.0	99.1
70	0	0	0	0	0	0	0	0	60- 70	3.878	441.8	100
80	0	0	0	0	0	0	0	0	70- 80	0	441.8	100
90	0	0	0	0	0	0	0	0	80- 90	0	441.8	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3°C
 Operators:
 Test Date: 19 December 2022

γ Range: 0 - 60DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

```

γ Range: 0 - 60DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 60DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```