

ELMARK HOLDING SE United Kingdom



CATALOGUE 2020



ELMARK®
The Brand of Electricity



**AIR CONDUIT ALUMINUM
ACCESSORIES FOR FANS**
PAGE 375



**END GRILLE
ACCESSORIES FOR FANS**
PAGE 377



**REVISION OPENING PVC
ACCESSORIES FOR FANS**
PAGE 380

SMART HOME CONTROL



**4 ZONES SWITCH
SMART HOME CONTROL**
PAGE 383



**WIFI RELAY
SMART HOME CONTROL**
PAGE 386



**RF DIMMER SWITCH
SMART HOME CONTROL**
PAGE 389



**WIFI SMART SOCKET
SMART HOME CONTROL**
PAGE 390



**WIRELESS SWITCH
SMART HOME CONTROL**
PAGE 392



**WIFI 4 CHANEL SWITCH
SMART HOME CONTROL**
PAGE 393



**Wi-Fi SMART CAMERA
SMART HOME CONTROL**
PAGE 398



**Wi-Fi SMART CAMERA
SMART HOME CONTROL**
PAGE 399



**INFRARED ALARM SENSOR
SMART HOME CONTROL**
PAGE 401



**VIDEO DOOR PHONE
SMART HOME CONTROL**
PAGE 402

DOORBELLS



**DOORBELL
WIRELESS DOORBELLS**
PAGE 406



SMART HOME CONTROL

IP20

ONE CHANNEL RECHARGEABLE LED PANEL REMOTE

3+0
standard
+extended

3 YEAR TOTAL WARRANTY




FUNCTION:

- To control single color LED lamp
- Removeable and stick easily
- With on/off state and touch operation indication
- Can remote control multiple controllers or lamps
- High precision touch chip with high sensitive & high stability touch control

TECHNICAL DATA:

- Wireless control (remote distance): 30m
- Standby time: 6 months
- Built-in rechargeable Li-Battery
- Working temperature: -30°C~55°C
- Product size: L86xW86xH13.5mm

Full info for the products, instructions, can be found at www.elmarkholding.eu



| Output signal | Li-battery capacity | Working current | Standby current | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|---------------------|-----------------|-----------------|-------------------|------------------|------------------|
| RF(2.4G) | 200mAh | <20mA | < 30μA | 1/200 | F | 99TOUCHUSB1 |

UNTIL SUPPLY
LAST




IP20

FOUR CHANNEL RECHARGEABLE LED PANEL REMOTE

3+0
standard
+extended

3 YEAR TOTAL WARRANTY




FUNCTION:

- To control LED one-four colors
- Removeable and stick easily
- With on/off state and touch operation indication
- Can remote control multiple controllers or lamps
- High precision touch chip with high sensitive & high stability touch control

TECHNICAL DATA:

- Wireless control (remote distance): 30m
- Standby time: 6 months
- Built-in rechargeable Li-Battery
- Working temperature: -30°C~55°C
- Product size: L86xW86xH13.5mm

Full info for the products, instructions, can be found at www.elmarkholding.eu



| Output signal | Li-battery capacity | Working current | Standby current | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|---------------------|-----------------|-----------------|-------------------|------------------|------------------|
| RF(2.4G) | 200mAh | <20mA | < 30μA | 1/200 | F | 99TOUCHUSB4 |

UNTIL SUPPLY
LAST



IP20

ONE CHANNEL FOUR ZONES REMOTE


3+0
standard
+extended
3 YEAR TOTAL
WARRANTY**FUNCTION:**

- To control single color LED lamp
- Removeable and stick easily
- With on/off state and touch operation indication
- Can remote control multiple controllers or lamps
- High precision touch chip with high sensitive & high stability touch control

TECHNICAL DATA:

- Wireless control (remote distance): 30m
- Standby time: 6 months
- Built-in rechargeable Li-Battery
- Working temperature: -30°C~55°C
- Product size: L86xW86xH13.5mm

Full info for the products, instructions, can be found at www.elmarkholding.eu



- Power — Turn on/off all zone light.
- Brightness slide.
- 1 2 3 — Short press recall scene. Long press 2s to save the current state into 1/2/3.
- 1 2 3 4 — Short press turn on zone light and select zone simultaneously, long press 2s turn off zone light. 4 zone control separately or synchronously, each zone could control multiple receivers.

| Output signal | Battery capacity | Working current | Standby current | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|------------------|-----------------|-----------------|-------------------|------------------|------------------|
| RF(2.4G) | 2xAAA | <20mA | < 20μA | 1/200 | D | 99TOUCHB1 |



IP20

FOUR CHANNEL FOUR ZONES REMOTE

3+0
standard
+extended
3 YEAR TOTAL
WARRANTY**FUNCTION:**

- To control one-four colours
- Removeable and stick easily
- With on/off state and touch operation indication
- Can remote control multiple controllers or lamps
- High precision touch chip with high sensitive & high stability touch control

TECHNICAL DATA:

- Wireless control (remote distance): 30m
- Standby time: 6 months
- Built-in rechargeable Li-Battery
- Working temperature: -30°C~55°C
- Product size: L86xW86xH13.5mm

Full info for the products, instructions, can be found at www.elmarkholding.eu



- Power — Turn on/off all zone light.
- Color slide.
- M — Short press play 10 builtin mode, long press run mode-cycle.
- BRIGHTNESS — Adjust dynamic mode speed or static color brightness, 10 levels.
- W — Short press turn on/off W channel, long press adjust W channel brightness.
- 1 2 3 4 — Short press turn on zone light and select zone simultaneously, long press 2s turn off zone light. 4 zone control separately or synchronously, each zone could control multiple receivers.

| Output signal | Battery capacity | Working current | Standby current | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|------------------|-----------------|-----------------|-------------------|------------------|------------------|
| RF(2.4G) | 2xAAA | <20mA | < 20μA | 1/200 | D | 99TOUCHB4 |





TOUCH AC TRIAC RF DIMMER

3+0
standard
+extended
3 YEAR TOTAL
WARRANTY

FUNCTION:


- Control is done by installed IOS or Android application
- To dim and switch single color dimmable LED lamps, traditional incandescent and halogen lights
- Ultra sensitive high strength glass touch panel with touch brightness slide in the middle and backlighting
- Triac and Mosfet dimmable
- Work with direct connected dimmable light
- Great compatibility with a variety of dimming remoter
- Leading edge dimming or trailing edge dimming set by dip switch
- Minimum brightness set by dip switch
- Change brightness, support push, long push operation

TECHNICAL DATA:

- Adopt 2.4GHz wireless technology
- Wireless control (remote distance): 30m
- Input voltage: 100-240VAC
- Output voltage: 100-240VAC
- Working temperature: -30°C~55°C
- Product size: L86xW86xH50mm

Download Skydance Application from Android market or Apple store.

Full info for the products, instructions, can be found at www.elmarkholding.eu



| Input voltage | Output voltage | Output current | Output power | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|----------------|-----------------|------------------|-------------------|------------------|------------------|
| 100- 240VAC | 100- 240VAC | 1Channel x 1.2A | 100- 240VAC-288W | 1/200 | D | 99TOUCH1 |



RF AC TRIAC ROTARY DIMMER

3+0
standard
+extended
3 YEAR TOTAL
WARRANTY

FUNCTION:

- Control is done by installed IOS or Android application
- To dim and switch single color dimmable LED lamps, traditional incandescent and halogen lights
- Ultra sensitive high strength glass touch panel with touch brightness slide in the middle and backlighting
- Triac and Mosfet dimmable
- Work with direct connected dimmable light
- Great compatibility with a variety of dimming remoter
- Leading edge dimming or trailing edge dimming set by dip switch
- Minimum brightness set by dip switch
- Rotate knob to change brightness, support push, long push operation

TECHNICAL DATA:

- Adopt 2.4GHz wireless technology
- Wireless control (remote distance): 30m
- Input voltage: 100-240VAC
- Output voltage: 100-240VAC
- Working temperature: -30°C~55°C
- Product size: L86xW86xH50mm

Download Skydance Application from Android market or Apple store.

Full info for the products, instructions, can be found at www.elmarkholding.eu

| Input voltage | Output voltage | Output current | Output power | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|----------------|-----------------|------------------|-------------------|------------------|------------------|
| 100- 240VAC | 100- 240VAC | 1Channel x 1.2A | 100- 240VAC-288W | 1/200 | D | 99DIMMERR |



IP20



SINGLE ZONE RF REMOTE CONTROLLER

3+0 standard +extended **3** YEAR TOTAL WARRANTY
FUNCTION:

- Match with single color dimming receiver- 99RECEIVER1
- Operate with LED indicator light
- Can match one or more receiver

- Standby time: 6 months
- CR2032 button battery power supply
- Product size: L107xW58.5xH9mm

TECHNICAL DATA:

- Working volatage: 3VDC
- Wireless control (remote distance): 30m

Full info for the products, instructions, can be found at www.elmarkholding.eu

| Output signal | Working voltage | Working current | Standby current | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|-----------------|-----------------|-----------------|-------------------|------------------|------------------|
| RF(2.4GHz) | 3VDC(CR2032) | <20mA | <10µA | 1/150 | D | 99REMOTE1 |



IP20



SINGLE ZONE RF RGBW REMOTE CONTROLLER

3+0 standard +extended **3** YEAR TOTAL WARRANTY
FUNCTION:

- Match with one channel and four channel dimming receivers- 99RECEIVER1 and 99RECEIVER4
- Suitable to single color, dual color, RGB, RGBW or RGB+CCT LED controller
- Operate with LED indicator light
- Can match one or more receiver

TECHNICAL DATA:

- Working volatage: 3VDC
- Wireless control (remote distance): 30m
- Standby time: 6 months
- Battery: 2 x AAA
- Product size: L107xW58.5xH9mm

Full info for the products, instructions, can be found at www.elmarkholding.eu

| Output signal | Working voltage | Working current | Standby current | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|-----------------|-----------------|-----------------|-------------------|------------------|---------------------|
| RF(2.4GHz) | 3VDC(CR2032) | <20mA | <10µA | 1/150 | D | 99RGBREMOTE1 |



IP20



FOUR ZONE RF RGBW REMOTE CONTROLLER

3+0 standard +extended **3** YEAR TOTAL WARRANTY
FUNCTION:

- Match with one channel and four channel dimming receivers- 99RECEIVER1 and 99RECEIVER4
- Four way control
- Suitable to single color, dual color, RGB, RGBW or RGB+CCT LED controller
- Operate with LED indicator light
- Can match one or more receiver

TECHNICAL DATA:

- Working volatage: 3VDC
- Wireless control (remote distance): 30m
- Standby time: 6 months
- Battery: 2 x AAA
- Product size: L122xW53xH17.5mm

Full info for the products, instructions, can be found at www.elmarkholding.eu

| Output signal | Working voltage | Working current | Standby current | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|-----------------|-----------------|-----------------|-------------------|------------------|---------------------|
| RF(2.4GHz) | 3VDC(CR2032) | <20mA | <10µA | 1/150 | D | 99RGBREMOTE4 |





IP20



FOUR CHANNEL CONSTANT VOLTAGE RECEIVER


3+0
standard
+extended
3 YEAR TOTAL
WARRANTY

FUNCTION:

- Four channel 2.4GHz RF wireless LED lighting dimming receiver
- Work as ON/OFF switch and RGBW controller with RGBW remote
- Can also be used for RGB, RGBW, 2 x dual colour, 4 x single color LED strips
- Full compatibility with a variety of single color, dual color and RGB/RGBW remotes
- Through jump, strobe, gradual change style, fine adjust color, realize thousands of powerful editing effect
- 32 change mode optional
- Changing mode or loop mode can be stored to 8 scenes, or timing run
- Control is done by remote control, dimmer switch and/or installed IOS or Android application
- For more power control it can be equipped with amplifier

TECHNICAL DATA:

- Wireless control (remote distance): 30m
- Dimming range: 0-100%
- Product size: L97xW33xH18mm



| Input voltage | Output current | Output power (12V) | Output power (24V) | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|-----------------|--------------------|--------------------|-------------------|------------------|------------------|
| 12-24 VDC | 4Channel 4 x 3A | 0 - 144W | 0 - 288W | 1/100 | D | 99RGBWF4 |



IP20



WIFI RELAY CONTROLLER

3+0
standard
+extended
3 YEAR TOTAL
WARRANTY

FUNCTION:



- Convert WiFi to RF signal
- It used to carry 1-16 constant voltage receiver with different channel number
- WiFi-Relay controller control up to 16 zones lamp with any light type
- Can not control lamp directly

Download Skydance Application from Android market or Apple store.

Full info for the products, instructions, can be found at www.elmarkholding.eu

TECHNICAL DATA:

- Input voltage: 5-24VDC
- Wireless control (remote distance): 30m
- Product size: D72xH18mm



| Input voltage | Output current | Output power (12V) | Output power (24V) | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|----------------|--------------------|--------------------|-------------------|------------------|------------------|
| 5-24 VDC | - | - | - | 1/100 | D | 99RWIFI |





IP20



ONE CHANNEL LED DIMMING RECEIVER


3+0
standard
+extended
3 YEAR TOTAL
WARRANTY

FUNCTION:

- One channel 2.4GHz RF wireless LED lighting dimming receiver
- Work as ON/OFF switch and dimming
- Control is done by remote control, dimmer switch and/or installed IOS or Android application
- For more power control it can be equipped with amplifier

TECHNICAL DATA:

- Input voltage: 5-36VDC
- Output power: 5VDC: 0-40W; 12VDC: 0-96W; 24VDC: 0-192W; 36VDC: 0-288W
- Dimming range: 0-100%
- Product size: L97xW33xH18mm



| Input voltage | Output current | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|----------------|-------------------|------------------|------------------|
| 5-36 VDC | 1Channel x 8A | 1/150 | D | 99RECEIVER1 |



IP20



FOUR CHANNEL LED DIMMING RECEIVER

3+0
standard
+extended
3 YEAR TOTAL
WARRANTY


FUNCTION:

- Four channel 2.4GHz RF wireless LED lighting dimming receiver
- Control is done by remote control, dimmer switch and/or installed IOS or Android application
- Work as ON/OFF switch and RGBW controller with RGBW remoter, create colorful static or dynamic effect
- Can also be used for RGB, RGBW, 2 x dual colour, 4 x single color LED strips
- Full compatibility with a variety of single color, dual color and RGB/RGBW remoters

- When control RGB/RGBW lamp, built in 30 change mode optional
- For more power control it can be equipped with amplifier

TECHNICAL DATA:

- Input voltage: 12-36VDC
- Output power: 12VDC: 0-240W; 24VDC: 0-480W; 36VDC: 0-720W
- Dimming range: 0-100%
- Product size: L97xW33xH18mm



| Input voltage | Output current | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|-----------------|-------------------|------------------|------------------|
| 12-36VDC | 4Channel 4 x 5A | 1/150 | D | 99RECEIVER4 |



IP20

ONE CHANNEL POWER REPEATER

3+0
standard
+extended
3 YEAR TOTAL
WARRANTY


FUNCTION:

- It's used along with 99RECEIVER1, in case we want to increase the output power, for the control of several light sources
- It can be used unlimited number of amplifiers, connected in parallel or
- successively without reflecting the sincronization of the control itself

TECHNICAL DATA:

- Input voltage: 5-36VDC
- Output power: 5VDC: 40W; 12V: 96W; 24V: 192W; 36V: 288W
- Output current: 1x8A
- Product size: L97xW33xH18mm

Full info for the products, instructions, can be found at www.elmarkholding.eu



| Input voltage | Output current | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|----------------|-------------------|------------------|--------------------|
| 5-36 VDC | 1Channel x 8A | 1/200 | D | 99REPEATER1 |



IP20

FOUR CHANNEL POWER REPEATER

3+0
standard
+extended
3 YEAR TOTAL
WARRANTY


FUNCTION:

- It's used along with 99RECEIVER4, in case we want to increase the output power, for the control of several light sources
- It can be used unlimited number of amplifiers, connected in parallel or
- successively without reflecting the sincronization of the control itself

TECHNICAL DATA:

- Input voltage: 12-36VDC
- Output power: 12V: 240W; 24V: 480W; 36V: 720W
- Output current: 1x8A
- Product size: L175xW45xH27mm

Full info for the products, instructions, can be found at www.elmarkholding.eu



| Input voltage | Output current | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|-----------------|-------------------|------------------|--------------------|
| 12-36VDC | 4Channel 4 x 5A | 1/200 | D | 99REPEATER4 |





IP20



AC TRIAC RF DIMMER

3+0
standard
+extended **3** YEAR TOTAL
WARRANTY

FUNCTION:


- AC phase cut RF dimmer
- Control is done by installed IOS or Android application
- Control is done by remote control
- To dim and switch single color dimmable LED lamps, traditional incandescent and halogen lights
- Triac and Mosfet dimmable
- Leading edge dimming or trailing edge dimming set by dip switch

by dip switch

- Minimum brightness set by dip switch

TECHNICAL DATA:

- Wireless control (remote distance): 30m
- Output voltage: 100-240VAC
- Output power: 240VAC: 288W
- Product size: L103xW67xH30mm



| Input voltage | Output current | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|-----------------|-------------------|------------------|-------------------|
| 100- 240VAC | 1Channel x 1.2A | 1/300 | D | 99DIMMERT1 |



IP20



AC TRIAC RF DIMMER SWITCH


3+0
standard
+extended **3** YEAR TOTAL
WARRANTY

FUNCTION:

- AC phase cut RF dimmer switch
- Control is done by installed IOS or Android application
- Control is done by remote control. Can accept up to 10 remote control
- Suitable to use with dimmer switch. Great compatibility with a variety of dimming remote
- Suitable to mounting in standard panel bottom box
- To dim and switch single color dimmable LED lamps, traditional incandescent and halogen lights
- Triac and Mosfet dimmable
- Leading edge dimming or trailing edge dimming set by dip switch
- Minimum brightness set by dip switch

TECHNICAL DATA:

- Wireless control (remote distance): 30m
- Input voltage: 100-240VAC
- Output voltage: 100-240VAC
- Output power: 240VAC: 240W
- Product size: L52xW25xH26mm



| Input voltage | Output current | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|----------------|-------------------|------------------|-------------------|
| 100- 240VAC | 1Channel x 1A | 1/200 | D | 99DIMMERMT |





IP20



ONE CHANNEL SMART WIFI GLASS TOUCH PANEL

3+0
standard
+extended
3 YEAR TOTAL
WARRANTY

FUNCTION:

- Touch ON/OFF
- Real-time turn ON/OFF lighting from anywhere
- Control is done from anywhere with IOS or Android mobile application
- Time setting function- turn ON/OFF at specified time after setting
- Through jump, strobe, gradual change style, fine adjust color, realize thousands of powerful editing effect
- Turn ON/OFF a gang of devices with one tap
- Control can be shared to another mobile phones
- Control electrical devices over Wi-Fi
- Supports max 8 enabled timing tasks
- EU standard
- Possibility to voice control with AMAZON ALEXA, Google Home(Stay tuned)
- Works with GOOGLE NEST

TECHNICAL DATA:

- Input voltage: 90-250VAC
- Output power: 400W
- Output current: 2A
- Frequency: 2.4Ghz
- Working temperature: 0°C-40°C (32°F-104°F).
- Humidity: 5%-90%RH, Non-condensing

Download EWeLink Application from Android market or Apple store.

Full info for the products, instructions, can be found at www.elmarkholding.eu

| Input voltage | Output current | Output power | Colour | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|----------------|--------------|--------|-------------------|------------------|------------------|
| 90-250V AC | 2A | 400 W | white | 1/1000 | D | 195020 |



IP20



195021

195022

WIFI SMART PLUG-IN SOCKET GERMAN/UK TYPE

3+0
standard
+extended
3 YEAR TOTAL
WARRANTY

FUNCTION:

- Turn ON/OFF electrical devices from anywhere
- Real time control status
- Control is done from anywhere with IOS or Android mobile application
- Time setting function- turn ON/OFF at specified time after setting
- Turn ON/OFF a gang of devices with one tap
- Control can be shared to another mobile phones
- Control electrical devices over Wi-Fi
- Supports max 8 enabled timing tasks
- German / UK standard
- Possibility to voice control with AMAZON ALEXA, Google Home(Stay tuned)
- Works with GOOGLE NEST
- Security mechanism: WEP/WPA-PSK/WPA2-PSK/WPA/WPA2/WAPI/WPS2

TECHNICAL DATA:

- Input voltage: 90-250VAC
- Output power: 2000W
- Output current: 10A
- Frequency: 2.4Ghz
- Working temperature: 0°C-40°C (32°F-104°F).
- Humidity: 5%-90%RH, Non-condensing

Download EWeLink Application from Android market or Apple store.

Full info for the products, instructions, can be found at www.elmarkholding.eu

| Socket Type | Input voltage | Output current | Output power | Packing/Box (pcs) | Product category | Catalogue number |
|-------------|---------------|----------------|--------------|-------------------|------------------|------------------|
| German | 90-250V AC | 10A | 2000 W | 1/900 | D | 195021 |
| UK | 90-250V AC | 10A | 2000 W | 1/200 | D | 195022 |





IP20



WIFI SMART PLUG-IN SOCKET GERMAN TYPE

3+0
 standard
 +extended
3 YEAR TOTAL
 WARRANTY
FUNCTION:

- Turn ON/OFF electrical devices from anywhere
- Real time control status
- Control is done from anywhere with IOS or Android mobile application
- Time setting function- turn ON/OFF at specified time after setting
- Turn ON/OFF a group of devices with one tap
- Control electrical devices over Wi-Fi
- Possibility to voice control with AMAZON ALEXA, Google assistant

TECHNICAL DATA:

Input voltage: 100-240VAC
 Output power: 3500W
 Output current: 16A
 Frequency: 2.4Ghz
 Working temperature: -10°C-50°C
 Size (LxWxH)mm: 108x56x72

Download "Tuya smart" Application from Android market or Apple store.

Full info for the products, instructions, can be found at www.elmarkholding.eu

| Socket Type | Input voltage | Output current | Output power | Packing/Box (pcs) | Product category | Catalogue number |
|-------------|---------------|----------------|--------------|-------------------|------------------|------------------|
| German | 100-240V AC | 16A | 3500 W | 1/100 | D | 195023 |





IP20



195001



195004

ONE AND TWO CHANNEL SMART SWITCH

3+0 standard
+extended **3** YEAR TOTAL WARRANTY

FUNCTION:

- One and Two channel wireless ON/OFF switch
- Real-time ON/OFF devices status provided to application from anywhere
- Control is done from anywhere with IOS or Android mobile application
- Time setting function- turn ON/OFF at specified time after setting
- Control can be shared to another mobile phones
- Control electrical devices over Wi-Fi
- Supports max 8 enabled timing tasks
- Possibility to voice control with AMAZON ALEXA, Google Home (Stay tuned)
- Works with GOOGLE NEST

TECHNICAL DATA:

- Input voltage: 90-250VAC
- Output power: 2000W per channel
- Output current: 10A per channel
- Frequency: 2.4Ghz
- Working temperature: 0°C-40°C (32°F-104°F).
- Humidity: 5%-90%RH, Non-condensing
- Product size: L88xW38xH23mm

Download EWeLink Application from Android market or Apple store.

Full info for the products, instructions, can be found at www.elmarkholding.eu

| Input voltage | Output current | Output power | Colour | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|----------------|--------------|--------|-------------------|------------------|------------------|
| 90-250V AC | 10A | 2200 W | white | 1/800 | D | 195001 |
| 90-250V AC | 2x10A | 2x2200 W | white | 1/ 800 | D | 195004 |



IP20



WIRELESS SMART SWITCH WITH POWER CONSUMPTION MEASUREMENT

3+0 standard
+extended **3** YEAR TOTAL WARRANTY

FUNCTION:

- Real-time ON/OFF control and monitoring status from energy usage in a period via App (KWH calculator)
- Check energy usage daily and monthly via App
- Control is done from anywhere with IOS or Android mobile application
- This device works perfectly with electric fan, air conditioner, humidifier, smart fish tank, watering system, etc.
- Time setting function- turn ON/OFF at specified time after setting
- Control can be shared to another mobile phones
- Control electrical devices over Wi-Fi
- Supports max 8 enabled timing tasks
- Possibility to voice control with AMAZON ALEXA, Google Home (Stay tuned)
- Works with GOOGLE NEST

TECHNICAL DATA:

- Input voltage: 90-250VAC
- Output power: 3500W
- Output current: 16A
- Frequency: 2.4Ghz
- Working temperature: 0°C-40°C (32°F-104°F).
- Humidity: 5%-90%RH, Non-condensing
- Product size: L114xW52xH32mm

Download EWeLink Application from Android market or Apple store.

Full info for the products, instructions, can be found at www.elmarkholding.eu

| Input voltage | Output current | Output power | Colour | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|----------------|--------------|--------|-------------------|------------------|------------------|
| 90-250V AC | 16A | 3500 W | white | 1/800 | D | 195003 |





IP20



195002



195030



195031

TEMPERATURE AND HUMIDITY MONITORING WIFI WIRELESS SWITCH

3+0
standard
+extended
3 YEAR TOTAL
WARRANTY

FUNCTION:

- Real-time ON/OFF control and monitoring status from temperature and humidity with sensor
- Can turn switch ON/OFF electrical devices without mounted
- sensor
- This device works perfectly with electric fan, air conditioner, humidifier,
- smart fish tank, watering system, etc
- Control is done from anywhere with IOS or Android mobile application
- Time setting function- turn ON/OFF at specified time after setting
- Control can be shared- temperature and humidity to another mobile phones
- Supports max 8 enabled timing tasks
- Possibility to voice control with AMAZON ALEXA,

- Google Home(Stay tuned)
- Works with GOOGLE NEST

TECHNICAL DATA:

- Input voltage: 90-250VAC
- Output power: 3500W
- Output current: 16A
- Frequency: 2.4Ghz
- Working temperature: 0°C-40°C (32°F-104°F).
- Humidity: 5%-90%RH, Non-condensing
- Product size: L114xW52xH32mm

SENSORS:

- 195030 - High-precision temperature & humidity sensor, -40°C/+80°C, 0~99.9% RH
- 195031 - Waterproof temperature sensor, IP68, -55°C/+125°C

| Input voltage | Output current | Output power | Colour | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|----------------|--------------|--------|-------------------|------------------|------------------|
| 90-250V AC | 16A | 3500 W | white | 1/800 | D | 195002 |



IP20



195006

SMART WIFI FOUR CHANNEL SWITCH

3+0
standard
+extended
3 YEAR TOTAL
WARRANTY

FUNCTION:

- Real-time ON/OFF switching electrical devices from anywhere
- This device is good for industrial control
- Three modes to work- Switch among interlock/self-locking/inching modes
- Possibility to turn on devices for 0,25-4 s
- Control each channel separately
- Control is done from anywhere with IOS or Android mobile application
- Time setting function- turn ON/OFF at specified time after setting
- Control can be shared to another mobile phones
- Control electrical devices over Wi-Fi
- Supports max 8 enabled timing tasks
- Possibility to voice control with AMAZON ALEXA, Google Home(Stay tuned)
- Works with GOOGLE NEST

TECHNICAL DATA:

- Input voltage: 90-250VAC & 5-24VDC
- Output power: 4x2200W
- Output current: 4x10A
- Frequency: 2.4Ghz
- Working temperature: 0°C-40°C (32°F-104°F).
- Humidity: 5%-90%RH, Non-condensing
- Product size: L145xW90
- Mounting: DIN rail

Download EWeLink Application from Android market or Apple store.

Full info for the products, instructions, can be found at www.elmarkholding.eu

| Input voltage | Output current | Output power | Packing/Box (pcs) | Product category | Catalogue number |
|-----------------------|----------------|--------------|-------------------|------------------|------------------|
| 90-250V AC / 5-24V DC | 4x10A | 4x2200 W | 1/ 350 | D | 195006 |



IP20

REMOTE CONTROL SWITCHES

3+0 standard
+extended **3** YEAR TOTAL
WARRANTY

DESCRIPTION:

The remote devices for lighting control work through sending a frequent signal from the key to the receiver, which commands the connected to it lighting bodies. The installation of the key can be done in a standard round bracket as the advantage of this product is that there is no additional requirement for wiring from it towards the receiver. Thanks to this the product is widely used in premises with build in installations where there is no ability for adding the additional cable layouts and expenses for their building are

reserved. The connection between the key and the receiver is through a frequent signal in the range -315Mhz – 433.92 Mhz.

TECHNICAL DATA:


- Battery: 12V 23A
- Input voltage: 220- 230 VAC
- Cordless control of lighting fixtures
- Frequency: 315Mhz-433.92 Mhz



| Description | Operating distance in open air (m) | Output power (per way) ESL/ LED lamp | Incandescent lamp | Packing/Box (pcs) | Product category | Catalogue number |
|----------------------|------------------------------------|--------------------------------------|-------------------|-------------------|------------------|------------------|
| One way output power | 50 | 200W | 600W | 1/60 | D | 99101 |



| Description | Operating distance in open air (m) | Output power (per way) ESL/ LED lamp | Incandescent lamp | Packing/Box (pcs) | Product category | Catalogue number |
|-----------------------|------------------------------------|--------------------------------------|-------------------|-------------------|------------------|------------------|
| Two ways output power | 50 | 200W | 600W | 1/60 | D | 99102 |



| Description | Operating distance in open air (m) | Output power (per way) ESL/ LED lamp | Incandescent lamp | Packing/Box (pcs) | Product category | Catalogue number |
|------------------------|------------------------------------|--------------------------------------|-------------------|-------------------|------------------|------------------|
| Three way output power | 50 | 200W | 600W | 1/60 | D | 99103 |



| Description | Operating distance in open air (m) | Output power (per way) ESL/ LED lamp | Incandescent lamp | Packing/Box (pcs) | Product category | Catalogue number |
|------------------------------|------------------------------------|--------------------------------------|-------------------|-------------------|------------------|------------------|
| Two ways output power- 2xE27 | 50 | 150W | 400W | 1/60 | D | 99104 |



In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

IP20



4 CHANNEL DIGITAL VIDEO RECORDERS

3+0 standard +extended
3 YEAR TOTAL WARRANTY

TECHNICAL DATA:

- Compression format: H.265
- Video system: NTSC/PAL
- Operation system: Linux- embedded
- Analog video-input/output: 4CH inputs / VGA and HDMI output
- IP Video Input: 2ch (only IP up to 6ch)
- Composite video input: up to 6ch (Analog video + IP video)
- Audio input/output: 1CH input /1CH output(RCA)
- Display resolution: Analog :1080N/720P/960H, IP:1080P/720P
- Display feature: single/Quad/S.E.Q.
- Record resolution: Analog :1080N/720P/960H, IP:1080P/720P
- Maximum input bandwidth: 8Mbps~16Mbps (default is 8Mbps, decrease one Analog channel can increase 4Mbps)
- Maximum output bandwidth: 16Mbps
- Maximum decode performance: 1080N:140fps
- Recording mode: Continuous/Manual/Motion detect
- Network type: Lan, DHCP, and DDNS
- HDD interface: 1SATA HDD, up to 6TB
- Multiplex operation: live display, record, playback, backup and network
- USB: 2xUSB(for mouse and backup/upgrade)
- PTZ control: yes (RS485)
- Mobile surveillance: Support Mobile Phones based on iPhone and Android operation system
- VGA/HDMI: 1024*768,1280*1024,1440*900,1920*1080
- Power supply: DC 12V/2A
- Dimension(WxDxH): 300x227x53mm
- Working temperature: -10°C~+55°C
- Working humidity: 10%~90%

| Model | Channel | Input voltage | Packing/Box (pcs) | Product category | Catalogue number |
|---------|---------|---------------|-------------------|------------------|------------------|
| EL-4004 | 4 | 12V DC | 1 | D | 195060 |



IP20



8 CHANNEL DIGITAL VIDEO RECORDERS

3+0 standard +extended
3 YEAR TOTAL WARRANTY

TECHNICAL DATA:

- Compression format: H.265
- Video system: NTSC/PAL
- Operation system: Linux- embedded
- Analog video-input/output: 8CH inputs / VGA and HDMI output
- IP Video Input: 4ch (only IP up to 12ch)
- Composite video input: up to 12ch (Analog video + IP video)
- Audio input/output: 1CH input /1CH output(RCA)
- Display resolution: Analog :1080N/720P/960H, IP:1080P/720P
- Display feature: 1/4/6/8/9/10/13/14S.E.Q.
- Record resolution: Analog :1080N/720P/960H, IP:1080P/720P
- Maximum input bandwidth: 16Mbps~32Mbps (default is 8Mbps, decrease one Analog channel can increase 4Mbps)
- Maximum output bandwidth: 32Mbps
- Maximum decode performance: 1080N:120fps
- Recording mode: Continuous/Manual/Motion detect
- Network type: Lan, DHCP, and DDNS
- HDD interface: 1SATA HDD, up to 6TB
- Multiplex operation: live display, record, playback, backup and network
- USB: 2xUSB(for mouse and backup/upgrade)
- PTZ control: yes (RS485)
- Mobile surveillance: Support Mobile Phones based on iPhone and Android operation system
- VGA/HDMI: 1024*768,1280*1024,1440*900,1920*1080
- Power supply: DC 12V/2A
- Dimension(WxDxH): 300x227x53mm
- Working temperature: -10°C~+55°C
- Working humidity: 10%~90%

| Model | Channel | Input voltage | Packing/Box (pcs) | Product category | Catalogue number |
|---------|---------|---------------|-------------------|------------------|------------------|
| EL-4008 | 8 | 12V DC | 1 | D | 195061 |



IP66



HD 2MP BULLET CAMERA IP66

3+0
standard
+extended
3 YEAR TOTAL
WARRANTY

CAMERA TECHNICAL DATA:

- IR Distance: up to 20m
- Image Sensor: 1/2.9" progressive CMOS
- Signal system: PAL/NTSC
- Frame Rate: AHD/TVI/CVI: P/25fps N/30fps/ CVBS: 960H
- Resolution: 2MP 1920(H)×1080(V)
- Lens: 3.6mm
- Day & Night: IR cut filter: 850nm
- Synchronization: internal
- Dwdr: support
- Communication: Up the coax, protocol

MENU:

- AGC: yes
- Day/Night Mode: EXT/auto/color/black and white)
- White balance: auto/manual
- BLC: yes
- S/N ratio: 40dB
- OSD: support

INTERFACE:

- Video Output: 1-channel BNC video output
- Swaitch Button: AHD/TVI/CVI/CVBS

| Model | Channel | Input voltage | Packing/Box (pcs) | Packing/Box (pcs) | Product category | Catalogue number |
|---------|---------|---------------|-------------------|-------------------|------------------|------------------|
| EL-2232 | 8 | 12V DC | max 3W | 1 | D | 195054 |



IP66



HD 2MP DOME CAMERA IP66

3+0
standard
+extended
3 YEAR TOTAL
WARRANTY

CAMERA TECHNICAL DATA:

- IR Distance: up to 15m
- Image Sensor: 1/2.9" progressive CMOS
- Signal system: PAL/NTSC
- Frame Rate: AHD/TVI/CVI: P/25fps N/30fps/ CVBS: 960H
- Resolution: 2MP 1920(H)×1080(V)
- Lens: 3.6mm
- Day & Night: IR cut filter: 850nm
- Synchronization: internal
- Dwdr: support
- Communication: Up the coax, protocol

MENU:

- AGC: yes
- Day/Night Mode: EXT/auto/color/black and white)
- White balance: auto/manual
- BLC: yes
- S/N ratio: 40dB
- OSD: support

INTERFACE:

- Video Output: 1-channel BNC video output
- Swaitch Button: AHD/TVI/CVI/CVBS

| Model | Channel | Input voltage | Packing/Box (pcs) | Packing/Box (pcs) | Product category | Catalogue number |
|--------|---------|---------------|-------------------|-------------------|------------------|------------------|
| EL-328 | 8 | 12V DC | max 3W | 1 | D | 195055 |



DVR AND CAMERA ACCESSORIES - CABLE SPLITTERS



1 to 4 or 1 to 8 power splitter power cable (power splitter connection)
Plug and play ready only for camera with DC power
For adapting power supply 12V2A

| Description | Power source type | Packing/Box (pcs) | Product category | Catalogue number |
|--------------------|-------------------|-------------------|------------------|------------------|
| 1-4 cable splitter | DC | 1 | D | 195062 |
| 1-8 cable splitter | DC | 1 | D | 195063 |



DVR AND CAMERA ACCESSORIES- POWER ADAPTOR



High quality supply for DVR cameras with over current protection, over voltage protection, overload protection and short-circuit protection

| Description | Input Voltage | Output Voltage | Current | Packing/Box (pcs) | Product category | Catalogue number |
|---------------|---------------|----------------|---------|-------------------|------------------|------------------|
| Power adaptor | 100-240V AC | 12V DC | 2A | 1 | D | 195065 |



DVR AND CAMERA ACCESSORIES- BNC CABLE



BNC video and power security camera cable. Suitable just for camera with DC power and supply DC power for security cameras
Plug and play connectors on both ends
It is used for CCTV cameras, DVRs, audio video systems. Compatible with all CCTV surveillance DVR camera system

| Description | Length (m) | Packing/Box (pcs) | Product category | Catalogue number |
|-------------|------------|-------------------|------------------|------------------|
| BNC cable | 18.29 | 1 | D | 195064 |





IP20



WI-FI SMART CAMERA

3+0
standard
+extended **3** YEAR TOTAL
WARRANTY

FUNCTION:

- Control is done from anywhere with IOS or Android mobil application
- Support TF recording & Cloud storage
- Two-way voice communication
- Motion detection voice alarm
- Detailed alarm sector setting
- Sending images
- Night vision

TECHNICAL DATA:

- Input voltage: 100-240VAC
- Output voltage: 5V
- Cover range: 10-15m
- Pixels: 100W pixels (720p)

Download V380 pro Application from Android market or Apple store.

- Full info for the products, instructions, can be found at www.elmarkholding.eu

| Type | Pixels | Cover range | Packing/Box (pcs) | Product category | Catalogue number |
|-------------------|-------------------|-------------|-------------------|------------------|------------------|
| indoor camera 100 | 100W pixels (720) | 10-15m | 1 | D | 195050 |



IP20



WI-FI SMART CAMERA

3+0
standard
+extended **3** YEAR TOTAL
WARRANTY

FUNCTION:

- Control is done from anywhere with IOS or Android mobil application
- Support TF recording & Cloud storage
- Two-way voice communication
- Motion detection voice alarm
- Detailed alarm sector setting
- Sending images
- Night vision

TECHNICAL DATA:

- Input voltage: 100-240VAC
- Output voltage: 5V
- Cover range: 10-15m
- Pixels: 200W pixels(1080p), H265

Download V380 pro Application from Android market or Apple store.

- Full info for the products, instructions, can be found at www.elmarkholding.eu

| Type | Pixels | Cover range | Packing/Box (pcs) | Product category | Catalogue number |
|--------------------|--------------------------|-------------|-------------------|------------------|------------------|
| indoor camera H265 | 200W pixels (1080), H265 | 10-15m | 1 | D | 195051 |





IP20



WI-FI CEILING SMART CAMERA

3+0
standard
+extended **3** YEAR TOTAL
WARRANTY
FUNCTION:

- Control is done from anywhere with IOS or Android mobil application
- Different view settings
- Support TF recording & Cloud storage
- Two-way voice communication
- Motion detection voice alarm & save alarm video
- Detailed alarm sector setting
- Sending images
- Night vision

TECHNICAL DATA:

- Input voltage: 100-240VAC
- Output voltage: 5V
- Cover range: 50m
- View angle: 360°
- Pixels: 200W pixels (1080p)

Download V380 pro Application from Android market or Apple store.

• Full info for the products, instructions, can be found at www.elmarkholding.eu

| Type | Pixels | Cover range | Packing/Box (pcs) | Product category | Catalogue number |
|--------------------|--------------------|------------------|-------------------|------------------|------------------|
| ceiling camera 200 | 200W pixels (1080) | 50m ² | 1 | D | 195052 |



IP66



WI-FI OUTDOOR SMART CAMERA IP66

3+0
standard
+extended **3** YEAR TOTAL
WARRANTY
FUNCTION:

- Control is done from anywhere with IOS or Android mobil application
- Different view settings
- Support TF recording & Cloud storage
- Two-way voice communication
- Motion detection voice alarm & save alarm video
- Detailed alarm sector setting
- Sending images
- Night vision
- General view

TECHNICAL DATA:

- Input voltage: 100-240VAC
- Output voltage: 12V
- Cover range: 25-30m
- Pixels: 100W pixels (720p)

Download V380 pro Application from Android market or Apple store.

• Full info for the products, instructions, can be found at www.elmarkholding.eu

| Type | Pixels | Cover range | Packing/Box (pcs) | Product category | Catalogue number |
|--------------------------|-------------------|-------------|-------------------|------------------|------------------|
| outdoor camera 100W IP66 | 100W pixels (720) | 25-30m | 1 | D | 195053 |





IP20



WIFI IP CAMERA WITH ALARM SYSTEM - KIT

3+0
standard
+extended
3 YEAR TOTAL
WARRANTY

FUNCTION:

- Magnetic Sensor: Under arm mode, when the door or window installed with magnetic sensor is opened, the magnetic sensor will send alarm signal to the main unit, the main unit will take video and send message to the smartphone.
- IR Sensor: When someone is detected by the infrared sensor, it will send alarm signal to the main unit. Under arm mode, the main unit will take video and send message to the smartphone.
- SOS Panic Button: When someone press the SOS panic button, it will send SOS signal to the main unit. Under arm mode, the main unit will send alarm signal and video to the users smartphone. Suitable for the care of children, the elderly and disabled people.
- Main Unit: IP camera with built-in Wi-Fi module. Receive wireless alarm signal from other security sensors. Under arm mode, after received signal, the main unit will take video and send message to the smartphone.
- Arm and disarm on smartphone
- View IP camera protected area from anywhere anytime.
- In arm mode IP camera will take video and send message when intruder enters the front door and

trigger the IR sensor, or break open the door/window contact, or panic button was pressed

- Night Vision: Supported by IP Camera
- Intercom: Two-way voice communication

TECHNICAL DATA:

- Working Distance: 100m (open area)
- IP Sensor Angle: Adjustable from 90° to 110°
- IP Camera Lens: HD 1080P

| Model | Description | Product category | Catalogue number |
|----------|---|------------------|------------------|
| EL-WFAK1 | WIFI IP camera with sensors and panic button- KIT | D | 195091 |





IP20



WIFI INFRARED ALARM SENSOR

3+0
standard
+extended **3** YEAR TOTAL WARRANTY

FUNCTION:

IR Sensor: When someone is detected by the infrared sensor, it will send alarm signal to the smartphone via APP.

TECHNICAL DATA:

- Working Distance: 30m (open area)
- IP Sensor Angle: 110°max 7m

| Model | Description | Product category | Catalogue number |
|--------|-------------------------------|------------------|------------------|
| EL-AK3 | WIFI IP Infrared alarm sensor | D | 195090 |



INFRARED ALARM WITH REMOTE CONTROL - KIT

3+0
standard
+extended **3** YEAR TOTAL WARRANTY

FUNCTION:

- IR Sensor: When someone is detected by the infrared sensor, alarm will be triggered.
- Magnetic Sensor: When the door or window installed with magnetic sensor is opened, the magnetic sensor will send signal to IR sensor and alarm will be triggered.
- Remote control: Arm/Disarm.

TECHNICAL DATA:

- IP Sensor Angle: 110°max 7m
- Alarm Volume: >100dB
- Working Distance: 30m (open area)

| Model | Description | Product category | Catalogue number |
|--------|---|------------------|------------------|
| EL-AK2 | Infrared alarm with remote control- kit | D | 195092 |



IP20



RECHARGEABLE WIFI SMART VIDEO DOOR BELL WITH DOOR CHIME

3+0
standard
+extended **3** YEAR TOTAL WARRANTY

FUNCTION:

- Intercom: Two-way voice communication and local intercom with 3 mobile users
- Monitoring: See and speak to visitors via the APP from anywhere
- Recording: TF card for storing the video recorder. Photo taking

OUTDOOR UNITS TECHNICAL DATA:

- Camera angle: 136°
- Battery: Li- 4000mA
- Night Vision: Supported
- Distance: 1-3m for night vision

| Model | Description | Product category | Catalogue number |
|--------------|---|------------------|------------------|
| EL-RWF1DP1DC | Rechargeable WIFI video doorbell switch with door chime | D | 195074 |





IP20

7 INCH WIFI SMART VIDEO INTERCOM DOORBELL SYSTEMS

3+0
standard
+extended **3** YEAR TOTAL
WARRANTY

FUNCTION:

- Monitoring: See and speak to visitors via the APP from anywhere
- Unlock door: when someone presses the button on the outdoor unit, the smartphone and the indoor unit will ring together. The local remote video intercom will be pushed to your smartphone APP, you can also unlock the door strike remotely by APP, or unlock by the door monitor unit. The door strike needs extra power supply.
- Recording: User can take photos or record video via APP
- Intercom: Two-way voice communication

INDOOR MONITORS TECHNICAL DATA:

- Connecting wire: 4- core
- Ring tone: 16 melody
- Working Voltage: 12VDC
- Resolution: 800x400
- Working Current: ≤ 1100mA
- Talking time: 120s±10%
- Monitoring time: 40s±10%

OUTDOOR UNITS TECHNICAL DATA:

- Working Voltage: 12VDC
- Working Current: ≤ 500mA
- IP Rating: IP44
- Body material: Metal: anti-oxidation and anti-vandal outdoor unit
- Night Vision: Supported

7 INCH WIFI SMART VIDEO INTERCOM DOORBELL SYSTEMS, SINGLE WAY- ONE BUTTON ONE MONITOR



| Model | Description | Monitors QTY | Voltage | Screen | Product category | Catalogue number |
|----------|----------------------------------|--------------|---------|--------|------------------|------------------|
| EL-WF1DP | Single way smart intercom system | 1 | 12VDC | 7 inch | D | 195071 |



7 INCH ADDITIONAL MONITOR FOR SINGLE WAY DOORBELL SYSTEM

Additional monitor is suitable only for single way intercom system. When a guest or visitor presses the doorbell button on the camera unit, the homeowner can use a few monitors to see who is requesting entry, speak with the caller, take a photo and unlock the door.

| Model | Description | Monitors QTY | Voltage | Screen | Product category | Catalogue number |
|--------|---------------------------------|--------------|---------|--------|------------------|------------------|
| EL-1BM | Additional monitor for EL-WF1DP | | 12VDC | 7 inch | D | 195077 |



7 INCH WIFI SMART VIDEO INTERCOM DOORBELL SYSTEMS, DOUBLE WAY- ONE UNIT WITH TWO BUTTON AND TWO MONITORS



| Model | Description | Monitors QTY | Voltage | Screen | Product category | Catalogue number |
|----------|----------------------------------|--------------|---------|--------|------------------|------------------|
| EL-WF2DP | Double way smart intercom system | 2 | 12VDC | 7 inch | D | 195072 |





7 INCH WIFI SMART VIDEO INTERCOM DOORBELL SYSTEMS, SINGLE WAY- ONE BUTTON AND TWO MONITORS

| Model | Description | Monitors QTY | Voltage | Screen | Product category | Catalogue number |
|------------|-------------------------------------|--------------|---------|--------|------------------|------------------|
| EL-WF1DP+1 | Single way intercom with 2 monitors | 2 | 12VDC | 7 inch | D | 195080 |



7 INCH WIFI SMART VIDEO INTERCOM DOORBELL SYSTEMS, SINGLE WAY- ONE BUTTON AND THREE MONITORS

| Model | Description | Monitors QTY | Voltage | Screen | Product category | Catalogue number |
|------------|-------------------------------------|--------------|---------|--------|------------------|------------------|
| EL-WF1DP+2 | Single way intercom with 3 monitors | 3 | 12VDC | 7 inch | D | 195076 |



7 INCH WIFI SMART VIDEO INTERCOM DOORBELL SYSTEMS, SINGLE WAY- ONE BUTTON AND FOUR MONITORS

| Model | Description | Monitors QTY | Voltage | Screen | Product category | Catalogue number |
|------------|-------------------------------------|--------------|---------|--------|------------------|------------------|
| EL-WF1DP+3 | Single way intercom with 4 monitors | 4 | 12VDC | 7 inch | D | 195078 |



7 INCH WIFI SMART VIDEO INTERCOM DOORBELL SYSTEMS, SINGLE WAY- ONE BUTTON AND FIVE MONITORS

| Model | Description | Monitors QTY | Voltage | Screen | Product category | Catalogue number |
|------------|-------------------------------------|--------------|---------|--------|------------------|------------------|
| EL-WF1DP+4 | Single way intercom with 5 monitors | 5 | 12VDC | 7 inch | D | 195079 |



In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.



IP20



WIFI SMART VIDEO DOOR BELL WITH TWO DOOR CHIMES

3+0
standard
+extended **3** YEAR TOTAL
WARRANTY

FUNCTION:

- Intercom: Two-way voice communication
- Monitoring: See and speak to visitors via the APP from anywhere
- Security: Built-in motion sensor. Once detected the human body, it can send an photo to the owner's e mail box, and send an alarm signal to the smartphone!

OUTDOOR UNITS TECHNICAL DATA:

- Camera: Reinforced CMOS
- Working Voltage: 12VDC
- Working Current: ≤ 500mA
- IP Rating: IP55
- Body material: Metal: anti-oxidation and anti-vandal outdoor unit
- Night Vision: Supported

| Model | Description | Voltage | Product category | Catalogue number |
|-------------|---|---------|------------------|------------------|
| EL-WF2DP2DC | WIFI video doorbell switch with 2 extra door chimes | 12VDC D | | 195073 |



DOORPHONE KIT

3+0
standard
+extended **3** YEAR TOTAL
WARRANTY

FUNCTION:

- Intercom: Two-way voice communication
- Unlock door strike

OUTDOOR UNITS TECHNICAL DATA:

- Working Voltage: 12VDC
- Working Current: ≤ 500mA
- IP Rating: IP44
- Body Material: Metal: anti-oxidation and anti-vandal outdoor unit
- Night Vision: Supported
- Two-wire connection

| Model | Description | Product category | Catalogue number |
|-----------|---------------|------------------|------------------|
| EL-1DP1IU | Doorphone kit | D | 195075 |





WIRELESS DOORBELLS



5020



5016



5019



WIRELESS DOORBELLS WITH LED FLASH LIGHT

| Catalogue number | Product category | QTY Transmitter/Receiver | Voltage (V) | Sound level db(A) | Volume levels | Music | Distance (m) | Packing/Box (pcs) |
|------------------|------------------|--------------------------|-------------|-------------------|-----------------|-------------|--------------|-------------------|
| 5020 | D | One/One | 220 | 65-85 | Low/Middle/High | 36 melodies | 80 | 1/60 |
| 5016 | D | One/One | 220 | 65-85 | Low/Middle/High | 36 melodies | 80 | 1/60 |
| 5019 | D | One/One | 220 | 65-85 | Low/Middle/High | 36 melodies | 80 | 1/60 |

Transmitter battery: 12V A23



In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.



5015



5018



WIRELESS DOORBELLS WITH LED FLASH LIGHT

| Catalogue number | Product category | QTY Transmitter/Receiver | Voltage (V) | Sound level db(A) | Volume levels | Music | Distance (m) | Packing/Box (pcs) |
|------------------|------------------|--------------------------|-------------|-------------------|-----------------|-------------|--------------|-------------------|
| 5015 | D | One/Two | 220 | 65-85 | Low/Middle/High | 36 melodies | 80 | 1/60 |
| 5018 | D | One/Two | 220 | 65-85 | Low/Middle/High | 36 melodies | 80 | 1/60 |

Transmitter battery: 12V A23



In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.



5023/1
5024



5023/2



WIRELESS DOORBELLS WITH LED FLASH LIGHT

| Catalogue number | Product category | QTY Transmitter/ Receiver | Transmitter Voltage (V) | Receiver Voltage (V) | Sound level db(A) | Volume levels | Music | Distance (m) | Packing/Box (pcs) |
|------------------|------------------|---------------------------|-------------------------|-----------------------|-------------------|-----------------|-------------|--------------|-------------------|
| 5023/1 | D | One/One | 12V 23A Battery | DC 3x1.5V AAA Battery | 70-85 | Low/Middle/High | 36 melodies | 80 | 1/60 |
| 5023/2 | D | One/Two | 12V 23A Battery | DC 3x1.5V AAA Battery | 70-85 | Low/Middle/High | 36 melodies | 80 | 1/60 |
| 5024 | D | One/One | 12V 23A Battery | 220V AC | 70-85 | Low/Middle/High | 36 melodies | 80 | 1/60 |



In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.



5025BL



5025WH



DIGITAL WIRELESS DOORBELLS WITH LED FLASH LIGHT

| Catalogue number | Product category | QTY Transmitter/ Reciever | Transmitter Voltage (V) | Receiver Voltage (V) | Sound level db(A) | Volume levels | Music | Distance (m) | Packing/Box (pcs) |
|------------------|------------------|---------------------------|-------------------------|----------------------|-------------------|-----------------|-------------|--------------|-------------------|
| 5025BL | D | One/One | 12V 23A Battery | DC 2x1.5V AA Battery | 70-85 | Low/Middle/High | 32 melodies | 120 | 1/60 |
| 5025WH | D | One/One | 12V 23A Battery | DC 2x1.5V AA Battery | 70-85 | Low/Middle/High | 32 melodies | 120 | 1/60 |



2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.



5021



5022



INFRARED INDUCTION DOORBELLS

| Catalogue number | Product category | Description | Voltage (V) | Sound level db(A) | Detection angle | Sensor detection distance (m) | Music | Packing/Box (pcs) |
|------------------|------------------|----------------------|-------------|-------------------|-----------------|-------------------------------|-------------|-------------------|
| 5021 | D | Doorbell with sensor | 4,5V DC | 85 | 100° | up to 7 | 36 melodies | 1/60 |
| 5022 | D | Doorbell & sensor | 4,5V DC | 85 | 100° | up to 7 | 36 melodies | 1/60 |

5021 - This is an electric appliance with inserted motion sensor. It is used for advisement for guests, visitors or customers. When there is a motion, it starts / there is a sound which advises that there is a visitor/customer/ in the premises. Working area - up to 7 meters

5022 - This is a complex product that combines two appliances. It is used for advisor for guests, visitors or customers. The sensor is installed to the place that we would like to know there is a motion/ visitor; this usually is the shop entrance, offices, warehouses and etc. The bell can be installed at a distance up to 130 m from the sensor which we will receive the signal for motion /visitor.

Working frequency: 315MHz/433.92 MHz



In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.



5012
5220



5001



BELL / BELL TRANSFORMER

| Catalogue number | Product category | Type | In (V) | Un (V) | Consumption (VA) | Sound level db(A) | Packing/Box (pcs) |
|------------------|------------------|------------------|--------|---------|------------------|-------------------|-------------------|
| 5012 | D | Bell | 230 | 8-12 | 3.6 | 70 | 1 / 12 / 240 |
| 5220 | D | Bell | 230 | 230 | 5 | 70 | 1 / 12 / 240 |
| 5001 | D | Bell transformer | 230 | 8/12/24 | 8 | - | 1 / 80 |

Mounting: on DIN-rail |



In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.